



VK-E-3000/R one section earthing rod set		EN 61230		EN 60832	CE
Cross section of the wire	Without wire	50 mm ²	70 mm ²	95 mm ²	120 mm ²
Thermic limit current	-	7,2 kA /1 s	7,2 kA /1 s	7,2 kA /1 s	7,2 kA /1 s
Dynamic limit current	-	16 kA	16 kA	16 kA	16 kA
Product code of the set	547138	547130	547132	547134	547136

- One section operating rod, type VK-E-3000 (rated voltage of the rod 120 kV)
- Phase clamp type KN-2003 / ATR
- Earthing clamp type KÖF-C-9004
- Wire with cross sections of 50, 70, 95 mm² (length of wire 4,5 m)



VK-E-3000/R one section earthing rod set		EN 61230		EN 60832	CE
Cross section of the wire	Without wire	50 mm ²	70 mm ²	95 mm ²	120 mm ²
Thermic limit current	-	10 kA /1 s	16 kA /1 s	20 kA /1 s	21 kA /1 s
Dynamic limit current	-	25 kA	40 kA	50 kA	53 kA
Product code of the set	547158	547150	547152	547154	547156

- One section operating rod, type VK-E-3000 (rated voltage of the rod 120 kV)
- Phase clamp type KN-9005 / PC
- Earthing clamp type KÖF-C-9004
- Wire with cross section of 50, 70, 95 mm² (length of wire 4,5 m)

